



## HID Aero™ X300 Output Control Interface Module

Controlling up to twelve general purpose outputs

### Key Features

- **Custom Rules Processing**  
Use X300 in conjunction with custom rules engine on X1100 to create elaborate rules for handling input states
- **Elevator Control**  
Use in conjunction with X1100 elevator processing engine to control elevator floor access
- **VertX V300 Replacement**  
Form/fit replacement
- **IO Module Encryption**  
Enhance security between intelligent controller and IO modules with AES encryption
- **Crypto Chips**  
Protect against malicious attacks to keep keys and passwords safe
- **Threat Levels**  
Define up to 7 different threat levels that are used to instantaneously adjust user access during lockdowns and lockouts
- **Mounting**  
Physically mount to DIN rails using accessory (sold separately)

### OUTPUT CONTROL INTERFACE MODULE SUPPORTING UP TO 12 GENERAL PURPOSE OUTPUTS

- **Open Architecture** - Work with a variety of software partners over time without any re-investment in hardware
- **Based on Mercury Technology** - Built on a tried and tested platform, operating in the most demanding access control enterprises for 25+ years
- **DIN Rail Mountable** - Use mounting accessory (sold separately) to easily attach housing to mechanical DIN rails
- **Easy to Understand LED Status Lights** - Status lights representing power, heartbeat, online/offline status, reader status, input status and relay status

The HID Aero Controller product line provides a complete and fully functional hardware, firmware, software library and tool infrastructure for access control software providers. This product line is ideal for access control providers who do not want to incur the ongoing costs of designing, manufacturing and maintaining panel hardware along with the critical access control logic that commonly resides locally in access control panels. The HID Aero Controller product line is the successor to HID's VertX® and EDGE®, and is based on HID Mercury technology, a panel technology supporting 4 million+ panels installed globally since the early 1990s.

The HID Aero X300 provides on-board IO support for up to twelve control points and four monitor points.

Attach the X300 to an X1100 intelligent controller to perform full access control processing or attach multiple X300s to control more outputs.

The X300 serves as a form and fit replacement for the VertX V300

## INTELLIGENT CONTROLLER & IO MODULE SYSTEM FEATURES

### Highly Configurable

- Change reader modes based on time thresholds, pre-alarm signals, for the benefits of functionality like a global lockdown
- Enable access rights or alerts for specific groups of users
- Create unique situational emergency alerts using highly detailed transaction information and data correlation features

### Sophisticated Threat Detection

- Duress signaled from keypad readers will notify the host for immediate action and

quick response in emergency situations

- Offline protection against improper card usage via local anti-passback capability
- Ability to monitor supervised input wiring to help identify system faults or malicious attacks

### Platform Security

- Encryption of data at rest provides privacy for data on the intelligent controller
- Monitor the health of the intelligent controller on the network by utilizing SNMPv3

- Ensure rogue devices cannot be plugged into the network by using 802.1X to implement port based network access control

### Hardware Design

- The Aero X1100 combines the capability of the legacy V1000 and V2000 enabling a simpler approach to installation - one SKU covers both use cases!
- Market leading maximum operating temperature allows for installation in harsh environments

## SPECIFICATIONS

<b>Input Voltage</b>	12 to 24 Vdc +/- 10%
<b>Maximum Input Current</b>	500 mA
<b>Intelligent Controller Communication</b>	2-wire RS-485, 2400 to 115K BPS, asynchronous
<b>Inputs</b>	5 supervised/unsupervised, standard EOL: 1k/1kΩ 1%, 1/4 watt
<b>Outputs</b>	12 Relays, Form-C with dry contacts, non-latching
<b>Relay Contact Rating</b>	2 A @ 30 Vdc resistive
<b>Operating Temperature</b>	32 to 158 °F (0 to 70 °C)
<b>Humidity</b>	5 to 85% RHNC
<b>Storage Temperature</b>	-67 to +185° F (-55 to +85° C)
<b>Dimension</b>	6.46" x 5.51" x 1.02" (164 mm x 140 mm x 26 mm)
<b>Weight</b>	326 g
<b>Certifications</b>	Certification: FCC Part 15 Subpart B, CE, BSMI, IC, AS/NZS, TCVN, KCC Safety: UL-294, IEC 62368-1, CB Scheme Hazardous Substances: RoHS (2011/65/EU & 2015/863), EU REACH (1907/2006), California Proposition 65
<b>HS Code</b>	8537.10.9
<b>ECCN</b>	EAR99

© 2020 HID Global Corporation/ASSA ABLOY AB. All rights reserved. HID, HID Global, the HID Blue Brick logo, the Chain Design, VertX, EDGE and HID Aero are trademarks or registered trademarks of HID Global or its licensor(s)/supplier(s) in the US and other countries and may not be used without permission. All other trademarks, service marks, and product or service names are trademarks or registered trademarks of their respective owners.

2020-03-09-pacs-aero-x300-controller-ds-en

PLT-05025



hidglobal.com

North America: +1 512 776 9000

Toll Free: 1 800 237 7769

Europe, Middle East, Africa: +44 1440 714 850

Asia Pacific: +852 3160 9800

Latin America: ++52 55 9171 1108