

VingCard C100

Electronic cylinders

The VingCard C100 E-Cylinder range is compatible with your VingCard Visionline system.

With a wide range of cylinder lengths and profiles for different regions, the C100 range compatible with a variety of standard and narrow profile lock cases. The range is suitable for both guest room doors and back of house applications where the door types can vary. C100 can be used with a variety of door types such as sliding doors, glass doors and aluminium profile doors.



FEATURES

- : Supports narrow style doors.
- : Supports glass doors and aluminium profile doors.
- : Rugged stainless steel finish.
- : Suitable for mixed VingCard installation.
- : Cylinder profiles for EURO, Scandinavian and Swiss cut-outs.
- : Quick and easy installation.
- : Fully compatible with Visionline and Lock Service.
- : Minimalistic and modern design.
- : LED for status visualisation (red/green/orange).
- : Battery capacity for approximately 10 openings per day for 2 years, but depending on surrounding temperature.

ASSA ABLOY
Global Solutions

The global leader in
door opening solutions

TECHNICAL DATA

Approvals:	CE
Dimensions:	43 x 32 mm (L x Ø)
Length:	Single version: 30 - 120 mm Double version: 30/30 - 120/120 mm
Finish:	Stainless steel brushed (ST)
Door Thickness:	DIN: Door leaf between 40 and 100 mm thick, in 10 mm increments. Scandinavian and Swiss: Door leaf between 35 and 95 mm thick, in 10mm increments.
Backset:	> 40 mm
Battery:	1 x Lithium CR2
Battery Life:	> 40,000 cycles (for max. 3 years)
Class of Protection:	IP 65 (not for outdoor use)
Operating Temperature Range:	-20 to +55 degrees Celsius
Humidity:	< 85% (condensation-free)
Status:	LED (red/green/orange)
RFID Technology:	Mifare Plus, Mifare UL EV1
Mobile Access Support:	No
Online Support:	No
Interface:	Micro USB firmware download and battery back up

