## **BASTION-M**

The Single-Leg Base Tripod Turnstile Gate with Reinforced Design. Its enlarged housing delivers added strength and durability, making it the perfect solution for managing high-intensity pedestrian traffic. Equipped with a dependable bidirectional servo-drive mechanism and strong locking system, Bastion-M ensures seamless operation in bustling areas.

Moreover, Bastion-M features an automatic antipanic system for emergencies. In such situations, the arms are swiftly lowered, enabling users to pass through without obstruction, prioritizing safety and smooth passage.



## ROBUST TRIPOD TURNSTILE WITH STYLISH DESIGN









PROTECTIVE LEVEL











## **Key features:**

- Seamlessly Integrates with Various Access Control and ID Systems;
- Ergonomically Crafted with Stylish Lines;
- Servo-Driven Tripod Turnstile with Anti-Panic (Drop-Arm) Functionl;
- Automatic Reset for Anti-Panic Feature;
- Perfect Fusion of Affordability and High Quality;
- Low Power Consumption;
- Backup Battery Power Connection for Continuous Operation;

- Silent Operation Ensures User Comfort;
- Compatible with Ramped Base Mobile Platform (TiSO Frame-M);
- Extensive Array of Accessories for Customization;
- Wired Remote Control Included in Standard Kit:
- Clear Guidance with 4 LED Indicators
- Built-In Space for RFID Readers Under Top Glass;
- ; Turnstile Supplied Ready for Installation.


\*option






## **Technical Specifications:**

connear specifications.	
Model	Bastion-M
Width, mm	815
Length, mm	793
Height, mm	1000
Passage width, mm	600
Mechanism	Servo-driven (Triservo-M)
Blocking system	Two electromagnetic stoppers
Emergency mode (fire-alarm)	Fail-safe (lowering the leash)
Drop arm function	Drop arm function can be activated when power is on Drop arm function activates automatically when power goes off
MCBF, cycles	5 000 000
Electrical Specifications:	
Maximum power consumption, W	55
Voltage	From the AC (100-240)V, 50/60Hz; from a DC source 12 V
Indication	DotLights®, RFIDLights®, EdgeLights® FloorLights®
Finishing	
Standard housing	Brushed SS AISI 304
Available housing	Brushed SS AISI 316; Polished SS AISI 304; Polished SS AISI 316; Powder coated RAL





Specifications are subject to change without prior notice.



