

## RFL200C Proximity Single Door Access Controller

July 31, 2014

### 1 Introduction

The intent of this document is to describe the specification of RFL200C standalone proximity access controller manufactured by IDTECK Co., Ltd. All the information is provided in detail for system architect and engineers designing access control system.

### 2 Description

The RFL200C standalone proximity access controller shall provide total control of access control for single door. With built-in 125KHz proximity reader, it shall dynamically control up to 512 users and provide event data safety mode once power failure and power fail safe or power fail secure locks function.

### 3 Mechanical Specification

- 3.1 The RFL200C proximity reader shall measure 4.9" x 1.8" x 0.7" (124 x 45 x 19.6mm). RFL200C shall arrive disassembled and contains following;
  - 3.1.1 A wall mounting plate
  - 3.1.2 The body that mounts to the wall mounting plate
- 3.2 The RFL200C shall have a dark pearl gray body
- 3.3 The RFL200C shall weight 80g (Packaged weight for shipping shall be 207g)

### 4 Electrical Specification

- 4.1 The RFL200C shall indicate its status through red and green LEDs.
- 4.2 The RFL200C standalone proximity reader shall operate on 12V. Max 150mA.
- 4.3 The RFL200C shall have Watch-dog timer & Power on Reset.

### 5 RFID reader Specification

- 5.1 The RFL200C shall include built-in 125KHz RF reader.
- 5.2 Reading Range of RFL200C shall vary depending on the types of the card that are used. The RFL200C shall accept following proximity cards with stated reading range.
  - 5.2.1 Passive cards that are stated below shall operate with the RFL200C and shall have declared reading range.
    - 5.2.1.1 IDC 80 card (ISO credit card size and thickness) shall have 4 inch (10 Cm) reading range.
    - 5.2.1.2 IDC 170 card (clamshell card) shall have 4 inch (10 Cm) reading range.
- 5.3 The RFL200 shall have 30ms reading time.

### 6 Communication Specification

- 6.1 The RFL200C shall support RS 485 Network communication (Max255). Ethernet[External LAN Converter Required]
- 6.2 The RFL200C shall support baud rate of 9600bps(default)

## **7 Environmental Specification**

### 7.1 Operating Temperature

7.1.1 The RFL200C shall operate temperature between -20°C ~ +50°C.

### 7.2 Operating Humidity

7.2.1 The RFL200C shall operate humidity between 10% ~ 90% RH(Non-condensing)

## **8 Certification and Approvals**

### 8.1 The RFL200C shall have following certification

8.1.1 FCC certification

8.1.2 KC certification

8.1.3 CE certification

8.1.4 RoHS certification

## **Technical Support Contact Information:**

### **Headquarters** : IDTECK Co., Ltd.

5F, Ace Techno Tower Bldg , 468, Gangseo-ro, Gangseo-gu, Seoul, 157-030, Korea

Tel : +82-2-2659-0055 Fax : +82-2-2659-0086

E-mail : webmaster@idteck.com Website : www.idteck.com

### **USA** : IDTECK Global Inc.

1555 Redondo Beach Blvd #100 Gardena, CA 90247

Tel. +1-702-421-2416

Email : sales@idteckglobal.com Website : www.idteckglobal.com

## **Disclaimer**

The information in the document has been carefully checked and reliable. IDTECK reserves the right to modify and revise the document without any notice. IDTECK holds no reliability for in accuracies in the document.

If you discover any discrepancy in this document please contact us via email listed above or phone.